

SUNFIRE®



RADIANT

DUAL FUEL
DIESEL / #2 KEROSENE



THE ULTIMATE ODORLESS HEATERS



SF160

160,000 BTU
Up to 3,700 Sq. Ft.

SF80

80,000 BTU
Up to 1,900 Sq. Ft.

SF120

120,000 BTU
Up to 2,800 Sq. Ft.

NO SMELL NO FUMES



SPECIFICATIONS	SF80	SF120	SF160
BTU/Hour:	80,000	120,000	160,000
Heating Space Capability	1,900 Sq. Ft.	2,800 Sq. Ft.	3,700 Sq. Ft.
Fuel Types:	Diesel, Kerosene, #2 Fuel Oil	Diesel, Kerosene, #2 Fuel Oil	Diesel, Kerosene, #2 Fuel Oil
Fuel Tank Capacity:	6 Gallons	14 Gallons	18 Gallons
Flow Rate:	Diesel: .58 GPH Kerosene: .56 GPH	Diesel: .85 GPH Kerosene: .78 GPH	Diesel: 1.14 GPH Kerosene: 1.05 GPH
Run Time (Approx.):	Up to 10 Hrs.	Up to 16 Hrs.	Up to 16 Hrs.
Dimensions:	19.75"W x 26"L x 27.75"H	28.5"W x 32"L x 33.75"H	32"W x 34"L x 43"H
Dry Weight:	85 lbs.	120 lbs.	160 lbs.
Wet Weight (Full Tank):	132 lbs.	210 lbs.	286 lbs.
Electrical:	120V .5A 60HZ 12V Pure Sine Power Inverter (800W Minimum)	120V 1.2A 60HZ 12V Pure Sine Power Inverter (800W Minimum)	120V 1.7A 60HZ 12V Pure Sine Power Inverter (800W Minimum)

RAPID ACCESS™ EASY MAINTENANCE HATCH

Hatch inside the burner assembly makes tuneups and nozzle changes quick and easy so you can spend less time on maintenance.

THERMOSTAT OPTION



All models can be regulated with any standard or battery-operated wall thermostat.

Thermostat not included with SF80 and SF120.
Thermostat included with SF160.

KEY FEATURES

- Low Noise
- Portable
- Clean & Odorless Heating
- Rubber Flat-Free Wheels
- Heavy-Duty Construction
- Dust-Free Heating Experience
- Safety Flame Sensor & Tip Switch
- Made in the USA



CALIFORNIA PROP 65

This product can expose you to ceramic fibers, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

- Not for indoor household residential use.
- Proper ventilation required.

