

4



## FMT 3 FLOW METER VARIOUS FLUIDS

THE LATEST DEVELOPMENT IN FLOW METER TECHNOLOGY

The FMT 3 is the latest development of turbine electronic flow meters from TECALEMIT. It's everything most meters in the market are missing.

Featuring a symmetric measurement chamber allowing multi-directional flow and a LEDilluminated display capable of being rotated. Additionally, users have the ability to separate the main body from its chamber, which is especially helpful for any future expansions & maintenance.


Furthermore, the FMT 3 Flow Meter is highly versatile and can be used with a range of fluids, offering customers ultimate flexibility.

## TECHNICAL SPECIFICATIONS & FEATURES

Multi directional flow				
Multi-directional flow				
Display can rotate in 90° increments				
Display can be mounted to fit any viewing angle				
Main body can be separated from the main chamber				
Turbine meter				
Flow rate min./max.:	1-30 gpm			
Nominal pressure max.:	10 bar			
External thread:	1" BSP			
Accuracy:	+/-1%			
Operating temperature:	-13 to +131°F			
Medium temperature:	-14 to 104°F			
Pulse ratio (pulser model only):	100:1			
Battery life (approx.):	5 years			
Weight:	0.53 lbs.			
Dimensions (W x D x H):	4.72" x 2.05" x 3.35"			

PART #	DESCRIPTION		
US253591006	FMT 3 TURBINE METER - NON-	PULSER	
US253591098	FMT 3 TURBINE METER - PULS	ER	







www.tecalemitusa.com | sales@tecalemitusa.com