

HORNET W85

DEF & DIESEL TRANSFER PUMPS

CONTINUOUS DUTY CYCLE TO KEEP OPERATIONS MOVING

The proprietary technology found only in TECALEMIT's Hornet W85 pumps make them one-of-a-kind systems. Featuring both vane and centrifugal combination systems, the Hornet W85 offers a continuous duty cycle.

Dispense longer distances, witness greater suction lifts, and experience higher flow rates with the Hornet W85. Designed to be used with drums, totes, and tanks, the Hornet W85 is versatile. Built only with the highest quality, it was created to stand the test of time.

Experience for yourself why the Hornet W85 is a customer favorite, boasting technology and performance with every gallon of fluid pumped.

HORNET W85 DEF

TECHNICAL SPECIFICATIONS & FEATURES

100% continuous duty cycle	
Thermal overload protection	
Capable of pushing product through hose lengths of 100 ft.	
Suction lift:	13 ft.
Power:	115/60 V/Hz
Discharge hose:	20 ft.
Max. pressure:	36 psi
Flow rate (with accessories):	10 gpm
Inlet:	3/4" BSP
Outlet:	3/4" BSP
Dimensions (W x D x H):	8" x 5" x 10"


PART #	DESCRIPTION
US108601200	HORNET W85 DEF TOTE PRO
US108600400	HORNET W85 DEF DRUM PRO
US108600006	HORNET W85 DEF PUMP ONLY
US108600005	HORNET W85 DEF PUMP & METER ONLY



CONTINUOUS
DUTY CYCLE



PATENTED
HYBRID PUMP
TECHNOLOGY



13 FT.
SUCTION LIFT



THERMAL
OVERLOAD
PROTECTION



PUSHES PRODUCT
THROUGH
25, 50, 100 FT.
HOSE LENGTHS



HORNET W85D DIESEL

TECHNICAL SPECIFICATIONS & FEATURES

100% continuous duty cycle	
Thermal overload protection	
Capable of pushing product through hose lengths of 100 ft.	
Suction lift:	13 ft.
Power:	115/60 V/Hz
Discharge hose:	13 ft.
Max. pressure:	36 psi
Flow rate (with accessories):	22 gpm
Inlet:	1" NPT
Outlet:	1" BSP
Dimensions (W x D x H):	8" x 5" x 10"

PART #	DESCRIPTION
US108701102	HORNET W85 DIESEL PUMP KIT
US916720003	HORNET W85 DIESEL PUMP ONLY
D FILTER MOUNT	HORNET W85 DIESEL FILTER MOUNT KIT

