


Novaflex 3261 OS & D Dock Hose with Built in Nipples

150# RF fixed flanges each end
Smooth black oil resistant cover
Temperature Range: -30°F (-35°C) to +200°F (+93°C)



Fuel Compatibility at ambient temperature:
Ethanol up to E85, E 100. Biodiesel up to B20

I.D.	lb/ft	lb/set Nipples
4	4.94	75
6	7.12	100
8	9.2	150
10	11.46	200
12	13.68	275

Meets USCG requirements

Novaflex 3265 Corrugated Dock Hose

Specially designed for barge unloading where flexibility and ease of handling are required. Special tire cord reinforcement with dual wire helix and corrugated cover enhances the characteristics. Tube resistant to 55% aromatic fuels. **Construction:**

Tube: NBR
Reinforcement: Polyester tire cord, dual wire helix.
Cover: Black NBR/PVC corrugated
Ends: Straight
Length 100 ft (max)
Temperature Range: -30°F (-35°C) to +200°F (+93°C)




Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3265BT-06000-00	6	7.20	4	30	30"	225	7.20
3265BT-08000-00	8	9.30	6	42	30"	225	10.84
3265BT-10000-00	10	11.50	6	60	30"	225	13.40
3265BT-12000-00	12	13.80	8	72	30"	225	17.25

Fuel Compatibility at ambient temperature:
Ethanol up to E85, E 100. Biodiesel up to B20

Meets USCG requirements

Novaflex 3265 Built-in Nipples Corrugated OS& D Hose

150# RF fixed flanges each end
Corrugated oil resistant black cover
Smooth black oil resistant cover
Temperature Range: -30°F (-35°C) to +200°F (+93°C)




Fuel Compatibility at ambient temperature:
Ethanol up to E85, E 100. Biodiesel up to B20

I.D.	lb/ft	lb/set Nipples
6	8.20	100
8	11.50	150
10	15.70	200
12	21.40	275

Novaflex 3267 Heavy Duty OS & D Dock Hose with Built in Nipples

150# RF fixed flanges each end
An extra heavy version of Novaflex 3261 designed for the extra rugged application, such as lightering to that extra abusive dock situation. Smooth black oil resistant cover.
Temperature Range: -30°F (-35°C) to +200°F (+93°C)




Fuel Compatibility at ambient temperature:
Ethanol up to E85, E 100. Biodiesel up to B20

I.D.	lb/ft	lb/set Nipples
6	7.40	100
8	10.50	150
10	14.90	200
12	20.0	275

Meets USCG requirements

Novaflex 3268 Built-in Nipples Heavy Duty Corrugated OS & D Dock Hose

An extra heavy version of Novaflex 3265 designed for the extra rugged application, such as lightering to that extra abusive dock situation.
Corrugated oil resistant black cover
Temperature Range: -30°F (-35°C) to +200°F (+93°C)



Fuel Compatibility at ambient temperature:
Ethanol up to E85, E 100. Biodiesel up to B20

I.D.	lb/ft	lb/set Nipples
6	8.30	100
8	11.70	150
10	16.10	200
12	22.00	275