

ABOVE GROUND TANK VALVES

ANTI-SYPHON VALVE

Application -

Reducing fire hazards and preventing fuel spillage should a line rupture.

The flow would automatically stop the syphon effect.

*Also available with pressure relief for thermal expansion (403PR).

Part Number - 403



Features -


- ✓ Precision machined valve seats
- ✓ Automatic shut off syphon effect
- ✔ Prevents fuel spillage
- ✓ No need to specify head settings when ordering
- ✓ Compatible with E-85 (Model E-403)
- ✓ PR opens 15-35PSI



Only from Universal! – No need to specify head settings! Everything is included to cover an operating range of 0' to 20'.

Construction -

- Zinc plated cast iron body
- Buna-N seals



	Thread	Weight				Thread	Weight		
Model	Size	(lbs.)	Α	В	Model	Size	(lbs.)	Α	В
403-34	3/4"	5.0	4-3/4"	2-3/8"	E-403-34	3/4"	5.0	4-3/4"	2-3/8"
403PR-34	3/4"	5.0	4-3/4"	2-3/8"	E-403PR-34	3/4"	5.0	4-3/4"	2-3/8"
403-10	1"	4.8	4-3/4"	2-3/8"	E-403-10	1"	4.8	4-3/4"	2-3/8"
403PR-10	1"	4.8	4-3/4"	2-3/8"	E-403PR-10	1"	4.8	4-3/4"	2-3/8"
403-15	1-1/2"	4.6	4-3/4"	2-3/8"	E-403-15	1-1/2"	4.6	4-3/4"	2-3/8"
403PR-15	1-1/2"	4.6	4-3/4"	2-3/8"	E-403PR-15	1-1/2"	4.6	4-3/4"	2-3/8"
403-20	2"	7.2	5-3/8"	2-1/2"	E-403-20	2"	7.2	5-3/8"	2-1/2"
403PR-20	2"	7.2	5-3/8"	2-1/2"	E-403PR-20	2"	7.2	5-3/8"	2-1/2"

Replacement Parts

Part Numbers	Description
403-10-A	1-1/2" x 1" Reducer Bushing
403-15-E	Poppet Guide
403-15-SK	Spring Kit (3/4",1" & 1-1/2")
403-20-SK	Spring Kit (2")
403-34-A	1-1/2" x 3/4" Reducer Bushing
403-20-SK	Spring Kit (2")

Notice: Universal Valve Co., products must be used in compliance with applicable federal, state, and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. Universal Valve Co., makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials, and specification are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation.