



Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

Date of Revision: None

Revision: 0

Section 1 - Chemical Product and Company Identification

1.1 Product Name: **VP Diesel Armor**

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmhurst, TX 78112, 210.635.7744

1.4 Recommended Use: Fuel System Treatment

1.5 **RESTRICTIONS on USE** **THIS STABILIZER IS FOR DIESEL ENGINES ONLY**

1.6 Emergency Response Number: **CHEMTREC 800-424-9300**

International Emergency Telephone Number: **+1-703-527-3887**

1.7 See Section 16.3 for CHEMTREC in Country Emergency Numbers

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Hazard Categories

Flammable liquid/vapor

Category 3

Specific Target Organs toxicity single exposure

Category 3

Eye Irritation

Category 2A

Skin Corrosion

Category 1B

Acute Toxicity (Oral)

Category 4

Acute Toxicity (Inhalation)

Category 4

Acute Toxicity (Dermal)

Category 4

Mutagenicity

Category 1B

Carcinogen

Category 1B

Aspiration Hazard

Category 1

Toxic to Aquatic Life Long Lasting Effects

Category 2

2.2 Signal Word: **Danger**

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act



2.3 Pictograms:

2.4 Hazard Statements

PHYSICAL HAZARDS:

H226: Flammable liquid and vapor

HEALTH HAZARDS:

H302: Harmful if swallowed
H304: May be fatal if swallowed and enter the airway
H314: Causes serious skin burns and eye damage
H312: Harmful in contact with skin
H319: Causes serious eye irritation
H340: May cause genetic defects
H350: May cause cancer
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
H372: Causes damage to organs through prolonged or repeated exposure

ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children
P201: Obtain special instructions before use. READ SDS BEFORE USE
P202: Do not handle until all safety precautions have been read and understood
P210: Keep away from sparks and open flames- No smoking
P240: Ground or bond container and receiving equipment
P241: Use explosion-proof equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P260: Do not breathe vapors
P264: Wash hands thoroughly after handling
P270: Do not eat, drink or smoke when using this product
P271: Use only outdoors or in well ventilated area
P273: Avoid release to the environment
P280: Wear protective gloves, clothing and eye protection

RESPONSE STATEMENTS:

P301 +P310+ P331: IF SWALLOWED: USA
Immediately call the National POISON CENTER at

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

800-222-1222. OUTSIDE USA Immediately call poison center or doctor. DO NOT induce vomiting
P303+P361+P353: IF ON SKIN Take off immediately all contaminated clothing. Rinse skin with water
P304+P340: IF INHALED. Remove to fresh air and keep comfortable for breathing
P305+P351: IF IN EYES rinse cautiously with water for at least 15 minutes
P308+P313: If exposed or concerned get medical attention
P362+P364: IF ON CLOTHING, take off contaminated clothing and wash it before reuse
P313+P337: If eye irritation persists get medical attention
H314: Get medical attention if you feel unwell
P330: Rinse mouth
P370: In case of fire use foam, carbon dioxide, dry chemical to extinguish fire
P376: Stop leaks if safe to do so.

STORAGE STATEMENTS:

P403+P405+P235: Store in a well-ventilated place, store locked up and keep cool

DISPOSAL STATEMENTS:

P501: Dispose of content and/or container in accordance with local, regional, national or international regulations

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Repeated exposure may cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS #	EC#	Chemical Name	Percent	Classification
N/A	N/A	Blend of Hydrocarbons, amines, and organic compounds	100%	None

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

3.2 Blend

Chemical Names	CAS#	EC#	Classification
Petroleum naphtha	64742-95-6	265-199-0	Asp. Tox. 1 H304, Muta. 1B H340, Carc. 1B H350
Pseudocumene	95-63-6	202-436-9	Flam. Liq. 2 H225, Skin Irrit. 2 H315, Eye Irrit 2, H319 Acute Tox. 4 H332, STOT SE 3 H335, Aquatic Chronic 2 H411
2-dimethylaminoethanol	108-01-0	203-542-8	Flam. Liq. 3, 226, Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B. H314, Acute Tox. 4 H332
Mesitylene	108-67-8	203-604-4	Flam. Liq. 3 H226, Skin Irrit. 2 H315, STOT SE 3 unknown H335, Aquatic Chronic 2 H411
Hemimellitene	526-73-8	208-394-8	Flam. Liq. 3 H226, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 H335
Diethylenimide oxide	110-91-8	203-815-1	Flam. Liq. 3, 226, Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B. H314, Acute Tox. 4 H332, STOT SE 3 H335
Dimethylbenzene	1330-20-7	215-535-7	Flam. Liq. 3 H226, Acute Tox 4 dermal H312, Skin Irrit. 2 H315, Eye Irrit 2, H319, Acute Tox 4 Inhalation
Cumol	98-82-8	202-704-5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 unknown H335, Aquatic Chronic 2 H411

3.3 Trade Secret Provision and Chemical Concentration Disclosure: In accordance with OSHA and GHS Regulations we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and are applicable to the hazards as identified in this Safety Data Sheet

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Causes serious skin burns.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic, or community medical support. The severity of outcome following an exposure may be more related to the time between the exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

5.1 General Fire Hazards: Use water to cool containers exposed to fire.

5.2 Hazardous Combustion Products: Avoid fumes of burning product.

5.3 Extinguishing Media: Carbon dioxide, dry chemical, foam.

5.4 Fire Fighting Equipment/Instructions: Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

6.1 Spill /Leak Procedures: Ventilate area spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

6.2 Spills: Avoid direct contact with material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

7.1 Handling Precautions: Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin or clothing. Keep container tightly closed. Avoid inhalation.

7.2 Storage Requirements: Store in a tightly closed container in a cool, dry, and well-ventilated area.

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Blend of Hydrocarbons, amines, and organic compounds	20-300 ppm TWA	20-300 ppm TWA

8.2.

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation are preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Viton is a Registered Trademark of DuPont Company.


8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing, flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms



VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

Section 9 - Physical and Chemical Properties

Physical State: Liquid
Appearance: Amber
Odor: Aromatic Hydrocarbon
Vapor Pressure: Not Available
Vapor Density (Air=1): >1
Specific Gravity (H₂O=1): 0.912 @ 68°F / 20°C
Relative Density: Not Available
Odor Threshold: Not Available
Flammability (solid, gas): Not Applicable.
Evaporation rate: Not Available
Partition coefficient octanol/water: Not Available

Water Solubility: Insoluble
Flash Point: 108°F (42.2°C) closed cup
Boiling Point/Range: 366 °F (169 °C)
Lower Explosive Limits (vol % in air): Not Available
Upper Explosive Limits (vol % in air): Not Available
Melting Point: Not Available
Viscosity: Not Available
Auto ignition Temperature: Not Available
Decomposition temperature: Not Available
pH: Not Available

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage

10.2 Polymerization: Hazardous polymerization has not been reported

10.3 Chemical Incompatibilities: Strong oxidizing agents

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide

10.5 Conditions to Avoid: Incompatibles

Section 11- Toxicological Information

11.1 Product Name	Results	Species	Dose	Exposure
Blend of Hydrocarbons, amines, and organic compounds	Oral LD50	Rat	1900 mg/kg	BASF Test
Blend of Hydrocarbons, amines, and organic compounds	Inhalation LC50	Rat	8 mg/l	None Listed
Blend of Hydrocarbons, amines, and organic compounds	Dermal LC50	Rabbit	500 mg/kg	None Listed

11.1.1 OECD Guideline 401 Tests results found in the European Chemical Agency Data Base shows that components of this product to cause Oral Toxicity.

11.1.2 OECD Guideline 403 Tests results found in the European Chemical Agency Data Base shows that components of this product to be Inhalation Toxicity.

11.1.3 OECD Guideline 402 Tests results found in the European Chemical Agency Data Base shows that components of this product to be Dermal Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin and/or Eye Contact

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

11.3 Aspiration Hazard: European Chemical Agency Data Base shows that components of this product may be fatal if swallowed and enters airways.

11.4 Mutagenicity: OECD Guideline 476 Tests results found in the European Chemical Agency Data Base show components of this product to cause genetic defects.

11.5 Skin Corrosion/Irritation: OECD Guideline 404 Tests results found in the European Chemical Agency Data Base shows that components of this product to cause skin burns. Repeated exposure may cause skin dryness or cracking.

11.6 Serious Eye Damage/Irritation: OECD Guideline 405 Tests results found in the European Chemical Agency Data Base shows that components of this product to cause serious eye irritation.

11.7 Specific Target Organ Toxicity (Single Exposure): European Chemical Agency Data Base shows that components of this product may cause drowsiness and dizziness and respiratory irritations.

11.8 Reproductive toxicity: OECD Guideline 421 Tests results found in the European Chemical Agency Data Base show no components of this product to cause damage to fertility or the unborn child.

11.9 Skin Sensitization OECD Guideline Tests results found in the European Chemical Agency Data Base show no components of this product to cause skin sensitivity.

11.10 Respiratory Sensitization OECD Guideline Tests results found in the European Chemical Agency Data Base show no components of this product to cause respiratory sensitivity.

11.11 Specific Target Organ Toxicity (Repeated Exposure): None

11.12 Signs and Symptoms: Effects due to exposure may include: nausea, diarrhea, coughing and headache. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline 453 Tests results found in the European Chemical Agency Data Base shows that components of this product to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Blend of Hydrocarbons, amines, and organic compounds	Not classifiable as a human carcinogen	Confirmed animal with unknown relevance to humans	Not listed	Not listed

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Blend of Hydrocarbons, amines, and organic compounds	Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment		

Toxicity: OECD Guideline 204 Test results found in the European Chemical Agency Data Base show components of this product to cause long-term toxicity to aquatic life.

12.2 Mobility: Floats on water

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! Container should be completely emptied prior to discard. Container with residues should be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 DOT Transport Information



ID No.: UN 2920

Shipping Name: Corrosive liquids, flammable, n.o.s. (2-dimethylaminoethanol, Pseudocumene)

Hazard Class: 8, (3)

Packing Group: II

Label: Corrosive, Flammable

Placard: Corrosive

Marking: MARINE POLLUTANT Pseudocumene when shipping ground greater than 119 gallons single container or any quantity by water

14.2 TDG Canadian Transport Information



ID No.: UN 2920

Shipping Name: Corrosive liquids, flammable, n.o.s. (2-dimethylaminoethanol, Pseudocumene)

Hazard Class: 8, (3)

Packing Group: II

Label: Corrosive, Flammable

Placard: Corrosive, Flammable

Marking: MARINE POLLUTANT Pseudocumene not regulated if shipped by road or rail

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

14.3 IMDG Transport Information



ID No.: UN 2920

Shipping Name: CORROSIVE LIQUIDS, FLAMMABLE, N.O.S. (2-dimethylaminoethanol, pseudocumene)

Hazard Class: 8, (3)

Packing Group: II

Label: Corrosive, Flammable

Placard: Corrosive, Flammable

Flash Point: (42.2 °C c.c.)

EmS Number: F-C, S-C

Label: Flammable

Placard: Flammable

Marking: Marine Pollutant Pseudocumene

14.4 ADR/RID Transport Information



ID No.: UN 2920

Shipping Name: Corrosive liquids, flammable, n.o.s. (2-dimethylaminoethanol, Pseudocumene)

Hazard Class: 8, (3)

Packing Group: II

Label: Corrosive, Flammable

Placard: Corrosive, Flammable

Marking : Marine Pollutant Pseudocumene

Classification Code : CF1

14.5 Australian Dangerous Goods Transport Information



ID No.: UN 2920

Shipping Name: Corrosive liquids, flammable, n.o.s. (2-dimethylaminoethanol, Pseudocumene)

Hazard Class: 8, (3)

Packing Group: II

Label: Corrosive, Flammable

Placard: Corrosive, Flammable


Marking: Marine Pollutant Pseudocumene

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

Marking: MARINE POLLUTANT The marine pollutant mark is only applicable for packages containing more than 5 liters for liquids

14.6



Use marking when shipping as a limited quantity ground in the US


DOT Transport Limited Quantity/Consumer Commodity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

14.7



Use marking when shipping as a limited quantity ground in the Canada


TDG Canada Transport Limited Quantity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

14.8



Use marking when shipping as a limited quantity by vessel.

IMDG Transport Limited Quantity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

ID No.: UN 2920

Shipping Name: CORROSIVE LIQUIDS, FLAMMABLE, N.O.S. (2-dimethylaminoethanol, pseudocumene)

Hazard Class: 8, (3)

Packing Group: II

Flash Point: (42.2° C c.c.)

EmS Number: F-C, S-C

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CERCLA Hazardous Substances and corresponding RQs: Dimethylbenzene 100 lbs., Cumol 5000 lbs

SARA Community Right-to-Know Program: Pseudocumene, Dimethylbenzene, Cumol

Clean Air Act: None

OSHA: All ingredients are regulated by 1910.1200

State Regulations

California prop. 65: Cumol Cancer

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

New Jersey: All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

Pennsylvania: All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.2 Canadian Regulation:

The following substances are specified on the public Portion of the Domestic Substances List (DSL): All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

15.3 Europe Regulations

Europe inventory:

All substances contained in this product are listed on the EU directives or are not required to be listed.

International Regulations:

Australian Inventory of Chemical Substance: All components of this product are on the Inventory or are exempt from Inventory requirements

National Existing Chemical Inventory in Taiwan: All components of this product are on Inventory or are exempt from Inventory requirements

Philippine Inventory of Chemicals and Chemical Substances: All components of this product are on the Inventory or are exempt from Inventory requirements

China Existing Chemical Inventory: All components of this product are on the Inventory or are exempt from Inventory requirements

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their purpose and on the condition that they assume the risk of their use.

16.2 References: CHEMTREC data base of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller on Line, European Chemical Agency Data Base and MSDS and SDS of chemicals in this mixture.

16.3 CHEMTREC in country emergency dial numbers:

CHEMTREC In-Country Dial Numbers	Local # Provided in Country	Toll Free in Country*	Greeting Language
AMERICAS			
CHEMTREC Argentina (Buenos Aires)	+(54)-1159839431		Latin American Spanish
CHEMTREC Brazil (Rio De Janeiro)	+(55)-2139581449		Portuguese
CHEMTREC Cayman Islands	+(1)-345-749-8392		English
CHEMTREC Chile (Santiago)	+(56)-225814934		Latin American Spanish
CHEMTREC Colombia *		01800-710-2151	Latin American Spanish
CHEMTREC Costa Rica*	+(506)-40003869		Latin American Spanish
CHEMTREC Mexico*		01-800-681-9531	Latin American Spanish
CHEMTREC Panama	+(507)-8322475		Latin American Spanish
CHEMTREC Peru (Lima)	+(51)-17071295		Latin American Spanish
CHEMTREC Trinidad and Tobago*	+(1)-868-224-5716		English
EUROPE			
CHEMTREC Austria (Vienna)	+(43)-13649237		German
CHEMTREC Belgium (Brussels)	+(32)-28083237		French, Flemish, German
CHEMTREC Bulgaria (Plovdiv)	+(359)-32570104		Bulgarian
CHEMTREC Croatia (Zagreb)	+(385)-17776920		Croatian
CHEMTREC Czech Republic (Prague)	+(420)-228880039		Czech
CHEMTREC Denmark	+(45)-69918573		Danish
CHEMTREC Estonia	+(372)-6681294		Estonian
CHEMTREC Finland (Helsinki)	+(358)-942419014		Finnish
CHEMTREC France	+(33)-975181407		French
CHEMTREC Germany *		0800-181-7059	German
CHEMTREC Germany (Frankfurt)	+(49)- 69643508409		German
CHEMTREC Greece (Athens)	+(30)-2111768478		Greek
CHEMTREC Hungary (Budapest)	+(36)-18088425		Hungarian
CHEMTREC Ireland (Dublin)	+(353)-19014670		English and Irish
CHEMTREC Italy *		800-789-767	Italian
CHEMTREC Italy (Milan)	+(39)-0245557031		Italian
CHEMTREC Latvia (Riga)	+(371)-66165504		Latvian
CHEMTREC Lithuania (Vilnius)	+(370)-52140238		Lithuanian
CHEMTREC Luxembourg	+(352)-20202416		French, German, Luxembourgish
CHEMTREC Netherlands	+(31)-858880596		Dutch
CHEMTREC Norway (Oslo)	+(47)-21930678		Norwegian
CHEMTREC Poland (Warsaw)	+(48)-223988029		Polish
CHEMTREC Portugal	+(351)-308801773		Portuguese
CHEMTREC Romania	+(40)-37-6300026		Romanian
CHEMTREC Russia*		8-800-100-6346	Russian
CHEMTREC Serbia ††	N/A	N/A	Serbian
CHEMTREC Slovakia (Bratislava)	+(421)-233057972		Slovak
CHEMTREC Slovenia (Ljubljana)	+(386)-18888016		Slovene/Slovenian
CHEMTREC Spain*		900-868538	European Spanish
CHEMTREC Spain (Barcelona)	+(34)-931768545		European Spanish
CHEMTREC Sweden (Stockholm)	+(46)-852503403		Swedish
CHEMTREC Switzerland (Zurich)	+(41)- 435082011		Swiss German, French and Italian
CHEMTREC Turkey (Istanbul)	+(90)-212-7055340		Turkish
CHEMTREC Ukraine	+(380)-947101374		Ukrainian
CHEMTREC UK (London)	+(44)-870-8200418		English

VP Diesel Armor

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Mexican Official Standard, NOM-018-STPS-2015, Harmonized System for the Identification and Communication
of Hazards and Risks of Hazardous Chemicals in the Workplace
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of
the Work Health and Safety Act

16.3 CHEMTREC in country emergency dial numbers continued:

MIDDLE EAST			
CHEMTREC Bahrain (Bahrain)	+(973)-16199372		Arabic
CHEMTREC Israel (Tel Aviv)	+(972)-37630639		Hebrew
CHEMTREC Saudi Arabia*	+(966)-8111095861		Arabic and English
CHEMTREC Kuwait National	+965-22274681		Arabic and English
SUB SAHARAN AFRICA			
CHEMTREC South Africa*		0-800-983-611	English
EAST ASIA			
CHEMTREC Hong Kong (Hong Kong)*		800-968-793	Cantonese
CHEMTREC Japan (Tokyo)	+(81)-345209637		Japanese
CHEMTREC South Korea*		00-308-13-2549	Korean
CHEMTREC South Korea	+(82) 070-7686-0086		Korean
CHEMTREC Taiwan*		00801-14-8954	Mandarin
SOUTHEAST ASIA			
CHEMTREC Indonesia*		001-803-017-9114	Indonesian
CHEMTREC Malaysia *		1-800-815-308	Malay
CHEMTREC Malaysia (Kuala Lumpur)	+(60)-327884561		Malay
CHEMTREC Philippines *		1-800-1-116-1020	Tagalog
CHEMTREC Philippines (Manila)	+(63) 2-395-3308		Tagalog
CHEMTREC Singapore*		800-101-2201	English and Mandarin
CHEMTREC Singapore	+(65)-31581349		English and Mandarin
CHEMTREC Thailand *		001-800-13-203-9987	Thai
CHEMTREC Vietnam (Hanoi)*	+(84)-444581938		Vietnamese
SOUTH ASIA			
CHEMTREC Bangladesh††	N/A	N/A	Bengali
CHEMTREC India *		000-800-100-7141	Hindi
AUSTRALIA & OCEANIA			
CHEMTREC Australia (Sydney)	+(61)-290372994		English
CHEMTREC New Zealand (Auckland)*	+(64)-98010034		English
*Phone numbers for countries marked with an asterisk must be dialed within the country			
*Phone numbers for countries marked with an asterisk must be dialed within the country.			
†† Phone numbers marked with a double dagger have a DID and greeting ONLY supplied by CHEMTREC			

16.4 SDS Preparation Date 11/06/2017

SDS Previous Issue Date: None

Prepared by SJC Compliance Education, Inc

16516 El Camino Real Suite 417

Houston, TX 77062