


Probe Description & Product Application	<p>Stainless Steel Mag Plus In-Tank Probe for Monitoring Gasoline, Retail Diesel Products & Water in both USTs and ASTs</p>	
--	--	---

	Part # & Description	Specific Products	Monitoring Functionality
Specific Products Monitored / Product Compatibility	Leak Detection / BIR - AccuChart Probes		
	1. 846397-1XX Stainless Steel (SS) In-Tank Probe with High Grade Polymer (HGP) Canister with Water Detection & 0.1GPH Testing Capability, UL	Gasohol (<=15% Ethanol)	A. 0.1 GPH static in-tank testing for USTs only
	2. 846397-2XX SS In-Tank Probe with HGP Canister with Water Detection & 0.2GPH Testing Capability, UL	Gasoline with <=7% Methanol and 8% TBA	B. 0.2 GPH static in-tank testing for USTs only
	3. 846391-1XX SS In-Tank Probe with Aluminum (AL) Canister with Water Detection & 0.1 GPH Testing Capability, UL	Gasoline with <=15% MTBE	C. 0.2 GPH Continuous Statistical Leak Detection (CSLD) for USTs only
	4. 846391-2XX SS In-Tank Probe with AL Canister with Water Detection & 0.2 GPH Testing Capability, UL	Gasoline with <=17% TAME	
		Leaded Gasoline	D. No Leak Detection / Inventory Only for USTs & ASTs
		Mineral Spirits	E. BIR – AccuChart for USTs only
		Premium Unleaded Gasoline	
		Regular Unleaded Gasoline	
		Gasoline with <=15% ETBE	
		Gasoline with <=12% TBA	
		Diesel (Fuel Oil #2)	
		Aviation Gas	
		Kerosene (Fuel Oil #1)	
		Bio Diesel (Low Density)	

Console Compatibility	Maximum Probes / Console	Probe Interface Modules				
		Module Part #	Module Description	# of Modules per Console	# of Probe Inputs per Module	Availability
TLS-450PLUS (8600 Series) with TLS-XB installed (3 max per system)	64 (32 with BIR)	332812-001	Universal Sensor Module (USM) Interface for Probes, Sensors, and DPLLD	Up to 4 - TLS-4XX	16	Sold Separately (either Factory Installed or as a Spare Module)
TLS4i (8601 Series)	4	No module required, probe input capability factory installed				
TLS4c (8601 Series)	2					
TLS-350/R/PLUS	16	329356-002	4-Input Probe Interface Module	4	4	Sold Separately (either Factory Installed or as a Spare Module)
TLS-300i	4	No module required, probe input capability factory installed				
TLS-300C	2					

Part # & Description	Float Size	Cable Lengths	Min/Max Probe Length	
Float Installation Kits	886100-XX0 Mag Plus Phase Separation Float Kit	4" (10.16cm)	5' (1.5m), 10' (3.05m), 20' (6.1m)	48" (1.2m) - 144" (3.66m)
	846400-3X0 Mag Plus Gasoline Float Kit	3" (7.62cm)		
	846400-1X0 Mag Plus Gasoline Float Kit	2" (5.08cm)		
	846400-0X1 Mag Plus Diesel Float Kit	4" (10.16cm)		
	846400-3X1 Mag Plus Diesel Float Kit	3" (7.62cm)		
	846400-1X1 Mag Plus Diesel Float Kit	2" (5.08cm)		
Other Installation Accessories	312020-952 4" (10.16cm) NPT Riser Cap and Ring Kit for In-Tank Probes 330020-282 4" (10.16cm) Threaded NPT Riser Cap for In-Tank Probes			
Specifications	Product	Water		
Measurement Accuracy	+/- 0.0300" (0.762mm)	+/- 0.0300" (0.762mm)		
Resolution - One Sample Reading	+/- 0.002857" (0.072571mm)	+/- 0.002857" (0.072571mm)		
Minimum Measurement - 2" (5.08cm) Float Kits	3.23" (8.2cm)	0.867" (2.2cm)		
Minimum Measurement - 3" (7.62cm) Float Kits	3.04" (7.72cm)	0.630" (1.6cm)		
Minimum Measurement - 4" (10.16cm) Float Kits	3.04" / 7.0" for Phase Sep.	0.630" (1.6cm)		
Operating (Working) Temperature Range	-40 to +122°F (-40 to +50°C)			
Third Party Evaluation / Agency Listings & Links	UL, cUL, ATEX, IECEx http://www.nwglde.org/evals/veeder_root_j.html			
Product Installation Guide Link	https://www.veeder.com/us/technical-document-library			

Example Installation

