## **ALTERNATING TREAD STAIR - ATS-9-68** APPROX WEIGHT: 211.23 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! \*\*\*ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE\*\*\* 23 5/8" -23 5/8" 20" 9 3/4" TOP STEP - SCALE: 1:12 149 5/8" STEP - SCALE: 1:12 2 1/4" 10 1/2" 76 3/4" 7 3/16" STEP **HEIGHT SPACING** 107 3/4" TOP STEP HEIGHT 33 1/2" 68° 50 1/2" 9 1/8" FOR INTERNAL USE ONLY PROJECT SIGN OFF **SALES** 23 1/2" 54 1/8"

ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON STANDARD FEATURES

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS

**MODEL NUMBER: ATS-9-68** CLIMB ANGLE: 68°

NUMBER OF STEPS: 15 (INCLUDING TOP STEP) TÖP STEP HEIGHT: 107 3/4" STEP HEIGHT SPACING: 7 3/16"

HANDRAIL HEIGHT: 12 1/4" OVERALL HEIGHT: 149 5/8" OVERALL LENGTH: 54 1/8" OVERALL WIDTH: 23 1/2" CHAIN GATES AT TOP STEP RUBBER BUMPER STRIP MAX CAPACITY IS 350 LBS

**TOUGH BAKED IN POWDER COATED YELLOW FINISH** 

SPECIAL FEATURES NONE

CONCEON ENGOIS				
	DIMENSION TOLERANCE ± 1/4" POWER			
	I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS			
	REPRESENTED SATISFIES DESIGN AND DIMENSION			
Α	REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO			
Р	CONFIRM PRODUCT AND INSTALLATION			
P	COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE			
	AND LOCAL REGULATIONS AND STANDARDS.			
R	ANY MODIFIED UNITS ARE NON-RETURNABI			
U				

## LΕ

ENG.

FAB.

[ ] As drawn [ ] As marked Signed:

**Printed Name:** 

٧

Α

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING				
DISTRIBUTOR'S NAME:		P.O.# X		
VESTIL MANUFAC	W.O.# X			
B.WOOD	DATE: 4/22/200	9 SALES: X		
EFERENCE: X	SCALE	: 1:30 <sup>FILE NAME:</sup>		
QUOTED LEAD TIME: X	QUOTE #	44-007-243		