

Materials

- Body:** Aluminum
- Main stem:** Stainless steel
- Packing:** Graphite with Teflon®
- Main Disc:** Viton®
- Inlet Size:** 1½" NPT



1290-0050

Features

- ◆ **Venturi-Type Shut-Off Mechanism** – for automatic shut-off.
- ◆ **Aluminum Body** – lighter in weight and easier to maneuver than other nozzles on the market.
- ◆ **Two-position hold-open device.**
- ◆ **One-Hand Control of Hold-Open Mechanism** – means easy setting of flow rate.
- ◆ **Right Angle Design** – provides larger lever area for better grips and easier control, permitting the nozzle to fit into awkward spaces close to walls and into corners.
- ◆ **Easily-Replaced Spout** – simply remove the spout retainer nut.
- ◆ **Built-In Outlet Check Valve** – meets all known requirements of the Division of Measurement Standards.
- ◆ **Dual Poppets** – make nozzle easy to open against high inlet pressure.

Design working pressure

- ◆ 50 psi (3.45 bar) maximum pressure.

Ordering Specifications

Product #	Description	Inlet Thread		lbs.	kg
		in.	mm		
1290-0050	New	1½"	38	6.8	3.1
1290-0055	Rebuilt	1½"	38	6.8	3.1
1290G-0050	New	1½"	38	6.8	3.1

Government National Stock #s:
 1290-0050; NSN 4930-01-290-0756
 1290G-0050; NSN 4930-01-352-1660 green anodized
 1290GS-0050; NSN 4930-01-352-1661 tan anodized
 (1290GS-AR50; tan anodized without kamlok coupler and dust plug)

Replacement Spout

Product #	O.D.		Length		Weight	
	in.	mm	in.	mm	lbs.	kg
5D-0125	1½"	35	8½"	215	1.5	0.68

1290 Series Instruction Sheet Order Number: **H09238PA**

OPW 1290 Automatic Shut-Off Nozzles

For Heavy-Duty, High-Flow Truck, Bus and Home Fuel Oil Delivery Service

