

GLACIER™ MULTIPURPOSE

Glacier™ is a cold weather multipurpose hose engineered for use in sub-zero applications while maintaining its kink-resistant flexibility and easy-reeling characteristics. Featuring an oil-resistant, synthetic rubber tube that is reinforced with a spiraled high tensile polyester yarn, Glacier™ is designed to provide a constant working pressure of 300 PSI and a 4:1 burst safety factor, capable of handling air, oil, gasoline, diesel, green fuels (biodiesel, biodiesel blends, ethanol, ethanol blends), kerosene, fuel oil and some chemicals. This hose comes standard with an embedded static wire.



Representative image photo see BRANDING below for product stamp.

RESISTANCE



Abrasion



Diesel Aromatic Fuels



Gasoline



Kerosene



Oil

BRANDING: Thermoid Glacier MP Hose
Size I.D. WP Made In USA

COVER COLOR: Black, Blue

CONSTRUCTION

TUBE: ECO, ARPM - Class A

- Capable of Handling Diesel, Kerosene and Gasoline
- Low Rating to -65°F, -54°C

COVER: ECO, ARPM - Class A

- Abrasion Resistant
- Easy to Reel Even at Extreme Cold Temperatures
- MSHA Approved Cover

REINFORCEMENT: 4-Spiral Polyester Yarn

- Provides a Working Pressure to 300 psi
- More Flexible than Braid Reinforced Hose
- Easier to Route Assemblies
- Easier to Coil and Handle
- Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque

TEMPERATURE RANGE: -65°F to +180°F, -54°C to +82°C

- Still Flexible at Extreme Low Temperatures

PACKAGING: Reels

- 300-500 ft. Reels Depending on I.D.

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22554166662▲	500	¼	6.35	0.63	15.88	4	300	2.07	1.50	38.10	0.15	0.22
22554246662	500	⅜	9.53	0.75	19.05	4	300	2.07	2.25	57.15	0.21	0.31
22554326662	500	½	12.70	0.94	23.81	4	300	2.07	3.00	76.20	0.30	0.45
22554486662	500	¾	19.05	1.25	31.75	4	300	2.07	4.50	114.30	0.39	0.58
22554646662	450	1	25.40	1.50	38.10	4	300	2.07	7.00	177.80	0.49	0.73
22554806662	300	1-¼	31.75	1.78	45.24	4	300	2.07	8.75	222.25	0.61	0.91
22554886662▲	300	1-⅜	34.93	1.88	47.63	4	300	2.07	9.25	234.95	0.68	1.01
22554966662▲	300	1-½	38.10	2.09	53.18	4	300	2.07	10.50	266.70	0.83	1.23

▲ = Non-stock