

DARI-PREEN CREAMERY

The Dari-Preen Creamery hose is designed for washdown service in creameries, dairies, packing houses, canneries and food processing plants. It features an EPDM tube and cover designed to resist scuffing and cracking and is color coded white to indicate washdown service and cleanliness. Dari-Preen is designed to handle hot water up to 212°F at 50 PSI, and is rated for working pressures up to 250 PSI on ½" I.D.



WARNING

Do not use this product as a steam hose or fuel (for example petroleum-based fuels and oils) hose.

CAUTION: This product is not recommended for environments where oil is present.



Representative image photo see BRANDING below for product stamp.

RESISTANCE



Abrasion



Heat



Ozone



Weathering

BRANDING: Size WP Dari-Preen Made In USA Month/Day/Year Time Stamp

COVER COLOR: White

- Color Indicates Washdown Service and/or Cleanliness

CONSTRUCTION

TUBE: EPDM, ARPM – Class C

- Heat Resistant
- Can Handle Hot Water to +200°F, +93°C at 50 psi

COVER: EPDM

- Heat Resistant
- Abrasion Resistant
- Ozone Resistant
- Weather Resistant
- Non-marking Cover

REINFORCEMENT: 4 -Spiral Polyester Yarn

- Provides a Working Pressure to 200-250 psi
- More Flexible than Braid Reinforced Hose
- Easier to Route Assemblies
- Easier to Coil and Handle
- Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque

TEMPERATURE RANGE: -40°F to +212°F, -40°C to +100°C

PACKAGING: Reels or 50 ft. Lengths – 1 Per Carton

- 600-700 ft. Reels Depending on I.D.
- Over 80% One Piece Reels
- Less Scrap
- Most Footage per Reel vs. Competition

PRESSURELESS CURE SYSTEM

- Minimal Cast (Natural Curvature of the Hose)
- Extends the Life of the Rubber Compounds

AIR MANDREL MANUFACTURING PROCESS

- No Internal Contamination of the Inside Diameter Due to the Lubricant
- Eliminates the Need for Customers to Flush the Hose

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00544808400	700	½	12.70	0.91	23.02	4	250	1.72	3.00	76.20	0.29	0.43
00544812400	600	¾	19.05	1.25	31.75	4	200	1.38	4.50	114.30	0.50	0.74
50 ft. Lengths												
00544812450	1 per carton	¾	19.05	1.25	31.75	4	200	1.38	4.50	114.30	0.50	0.74